

KuCoin API

KuCoin WebSocket and REST client — spot and futures market-data plus authenticated trading.

Overview

Kucoin is an international multi-language cryptocurrency exchange. It offers some APIs to access Kucoin data. The following APIs are supported:

At a glance

COMPONENT CLASS

`TsgcWSAPI_Kucoin`

STANDARDS / SPEC

[KuCoin API documentation](#)

TRANSPORTS

TCP, TLS

PLATFORMS

Windows, macOS, Linux, iOS, Android

FRAMEWORKS

VCL, FireMonkey, Lazarus / FPC, .NET

EDITION

Standard / Professional / Enterprise

Features

- Native Delphi implementation with full ANSI/Unicode support.

Technical specification

Standards & specs	KuCoin API documentation
Component class	<code>TsgcWSAPI_Kucoin</code> (unit <code>sgcWebSocket_API_Kucoin</code>)
Frameworks	VCL, FireMonkey, Lazarus / FPC, .NET
Platforms	Windows, macOS, Linux, iOS, Android

Main properties

The principal published / public properties used to configure and drive the component. Consult the online help for the full list.

<code>Client</code>	Published or public property used to configure or query the component.
<code>OnKucoinHTTPException</code>	Published or public property used to configure or query the component.
<code>Kucoin</code>	Published or public property used to configure or query the component.
<code>RawMessages</code>	Published or public property used to configure or query the component.
<code>REST_API</code>	Published or public property used to configure or query the component.
<code>Version</code>	Published or public property used to configure or query the component.

Main methods

The principal public methods exposed by the component.

<code>SubscribeIndexPrice()</code>	Public function exposed by the component.
<code>UnSubscribeIndexPrice()</code>	Public function exposed by the component.
<code>SubscribeOrderBookChanged()</code>	Public function exposed by the component.
<code>UnSubscribeOrderBookChanged()</code>	Public function exposed by the component.
<code>SubscribeTradeOrders()</code>	Public function exposed by the component.
<code>UnSubscribeTradeOrders()</code>	Public function exposed by the component.

`SubscribeMarginTradeOrders()`

Public function exposed by the component.

`UnSubscribeMarginTradeOrders()`

Public function exposed by the component.

`SubscribeStopOrder()`

Public function exposed by the component.

`UnSubscribeStopOrder()`

Public function exposed by the component.

Quick Start

Drop the component on a form, configure the properties below and activate it. The snippet that follows shows the typical **Binance | Connect WebSocket API** configuration sourced from the online help.

About this scenario. In order to connect to Binance WebSocket API, just create a new Binance API client and attach to TsgcWebSocketClient.

Delphi (VCL / FireMonkey)

```
oClient := TsgcWebSocketClient.Create(nil);
oBinance := TsgcWSAPI_Binance.Create(nil);
oBinance.Client := oClient;
oClient.Active := True;
```

C++ Builder

```
TsgcWebSocketClient *oClient = new TsgcWebSocketClient(NULL);
TsgcWSAPI_Binance *oBinance = new TsgcWSAPI_Binance(NULL);
oBinance->Client = oClient;
oClient->Active = true;
```

.NET (C#)

```
TsgcWebSocketClient oClient = new TsgcWebSocketClient();
TsgcWSAPI_Binance oBinance = new TsgcWSAPI_Binance();
oBinance.Client = oClient;
oClient.Active = true;
```

Common scenarios

The following scenarios are lifted verbatim from the online help. Each shows the configuration and method calls needed to drive the component through a specific real-world flow.

1 · Bitmex | Connect WebSocket API

In order to connect to Bitmex WebSocket API, just create a new Bitmex API client and attach to TsgcWebSocketClient.

Delphi (VCL / FireMonkey)

```
oClient := TsgcWebSocketClient.Create(nil);
oBitmex := TsgcWSAPI_Bitmex.Create(nil);
oBitmex.Client := oClient;
oClient.Active := True;
```

C++ Builder

```
TsgcWebSocketClient oClient = new TsgcWebSocketClient();
TsgcWSAPI_Bitmex oBitmex = new TsgcWSAPI_Bitmex();
oBitmex->Client = oClient;
oClient->Active = true;
```

.NET (C#)

```
TsgcWebSocketClient oClient = new TsgcWebSocketClient();
TsgcWSAPI_Bitmex oBitmex = new TsgcWSAPI_Bitmex();
oBitmex.Client = oClient;
oClient.Active = true;
```

2 · Coinbase | Connect WebSocket API

In order to connect to Coinbase WebSocket API, just create a new Coinbase API client and attach to TsgcWebSocketClient. See below an example:

Delphi (VCL / FireMonkey)

```
oClient := TsgcWebSocketClient.Create(nil);
oCoinbase := TsgcWSAPI_Coinbase.Create(nil);
oCoinbase.Client := oClient;
oClient.Active := True;
```

C++ Builder

```
TsgcWebSocketClient oClient = new TsgcWebSocketClient();
TsgcWSAPI_Coinbase oCoinbase = new TsgcWSAPI_Coinbase();
oCoinbase->Client = oClient;
oClient->Active = true;
```

.NET (C#)

```
TsgcWebSocketClient oClient = new TsgcWebSocketClient();
TsgcWSAPI_Coinbase oCoinbase = new TsgcWSAPI_Coinbase();
oCoinbase.Client = oClient;
oClient.Active = true;
```

3 · Kucoin | Connect WebSocket API

In order to connect to Kucoin WebSocket API, just create a new Kucoin API client and attach to TsgcWebSocketClient.

Delphi (VCL / FireMonkey)

```
oClient := TsgcWebSocketClient.Create(nil);
oKucoin := TsgcWSAPI_Kucoin.Create(nil);
oKucoin.Client := oClient;
oClient.Active := True;
```

C++ Builder

```
TsgcWebSocketClient *oClient = new TsgcWebSocketClient();
TsgcWSAPI_Kucoin *oKucoin = new TsgcWSAPI_Kucoin();
oKucoin->Client = oClient;
oClient->Active = true;
```

.NET (C#)

```
TsgcWebSocketClient oClient = new TsgcWebSocketClient();
TsgcWSAPI_Kucoin oKucoin = new TsgcWSAPI_Kucoin();
oKucoin.Client = oClient;
oClient.Active = true;
```

4 • Kucoin | Futures Connect WebSocket API

In order to connect to Kucoin WebSocket API, just create a new Kucoin API client and attach to TsgcWebSocketClient.

Delphi (VCL / FireMonkey)

```
oClient := TsgcWebSocketClient.Create(nil);
oKucoin := TsgcWSAPI_Kucoin_Futures.Create(nil);
oKucoin.Client := oClient;
oClient.Active := True;
```

C++ Builder

```
TsgcWebSocketClient *oClient = new TsgcWebSocketClient();
</code><code class="delphi">TsgcWSAPI_Kucoin_Futures </code><code class="cpp">*oKucoin = new </c
oKucoin->Client = oClient;
oClient->Active = true;
```

.NET (C#)

```
TsgcWebSocketClient oClient = new TsgcWebSocketClient();
</code><code class="delphi">TsgcWSAPI_Kucoin_Futures </code><code class="csharp">oKucoin = new <
oKucoin.Client = oClient;
oClient.Active = true;
```

5 • Binance | Subscribe WebSocket Channel

Binance offers a variety of channels where you can subscribe to get real-time updates of market data, orders... Find below a sample of how to subscribe to a Ticker:

Delphi (VCL / FireMonkey)

```

oClient := TsgcWebSocketClient.Create(nil);
oBinance := TsgcWSAPI_Binance.Create(nil);
oBinance.Client := oClient;
oBinance.SubscribeTicker('bnbbtc');

procedure OnMessage(Connection: TsgcWSConnection; const aText: string);
begin
  // here you will receive the ticker updates
end;

```

C++ Builder

```

TsgcWebSocketClient *oClient = new TsgcWebSocketClient(NULL);
TsgcWSAPI_Binance *oBinance = new TsgcWSAPI_Binance(NULL);
oBinance->Client = oClient;
oBinance->SubscribeTicker("bnbbtc");

void OnMessage(TsgcWSConnection *Connection, const string aText)
{
  // here you will receive the ticker updates
}

```

.NET (C#)

```

TsgcWebSocketClient oClient = new TsgcWebSocketClient();
TsgcWSAPI_Binance oBinance = new TsgcWSAPI_Binance();
oBinance.Client = oClient;
oBinance.SubscribeTicker("bnbbtc");

void OnMessage(TsgcWSConnection Connection, const string aText)
{
  // here you will receive the ticker updates
}

```

6 · Bitmex | Subscribe WebSocket Channel

Bitmex offers a variety of channels where you can subscribe to get real-time updates of market data, orders... Find below a sample of how subscribe to a Trade Channel:

Delphi (VCL / FireMonkey)

```
oClient := TsgcWebSocketClient.Create(nil);
oBitmex := TsgcWSAPI_Bitmex.Create(nil);
oBitmex.Client := oClient;
oBitmex.Subscribe(btmTrade, 'XBTUSD');
procedure OnBitmexMessage(Sender: TObject; const aTopic: TwsBitmexTopics; const aMessage: string)
begin
  // here you will receive the trade updates
end;
```

C++ Builder

```
TsgcWebSocketClient oClient = new TsgcWebSocketClient();
TsgcWSAPI_Bitmex oBitmex = new TsgcWSAPI_Bitmex();
oBitmex->Client = oClient;
oBitmex->Subscribe(btmTrade, "XBTUSD");
void OnBitmexMessage(Sender: TObject; const aTopic: TwsBitmexTopics; const aMessage: string)
{
  // here you will receive the trade updates
}
```

.NET (C#)

```
TsgcWebSocketClient oClient = new TsgcWebSocketClient();
TsgcWSAPI_Bitmex oBitmex = new TsgcWSAPI_Bitmex();
oBitmex.Client = oClient;
oBitmex.Subscribe(btmTrade, "xbtusd");
void OnBitmexMessage(Sender: TObject; const aTopic: TwsBitmexTopics; const aMessage: string)
{
  // here you will receive the tradeupdates
}
```

Sources used to build this document

Every external claim links back to a primary source. The online-help references decode the canonical deep-link the company maintains for this component.

Primary standard / spec — KuCoin API documentation

www.kucoin.com/docs/welcome/general-introduction

Online help — component page

www.esegece.com/help/sgcWebSockets/Components/APIs/API/API_Kucoin.htm

Delphi demo project (in the sgcWebSockets package)

`Demos\05.Crypto\11.Kucoin`

.NET demo project (in the sgcWebSockets package)

`.net\demos\05.Crypto\11.Kucoin`

Component page

www.esegece.com/products/websockets/apis/kucoin/

Product page

www.esegece.com/products/websockets/

Document scope. This document covers the publicly-documented surface of the KuCoin API component shipped with sgcWebSockets. For full property, method and event reference consult the online help linked above.